Instructions E43 - Welding (optional)

Assume PM-filterable = PM10-filterable = PM2.5-filterable.

Emission Calculations Procedures:

Facilities may use the default emission factors with Equation 1 to estimate PM-filterable emissions.

 $E = Q \times EF \times (1 - C) / 2000 \text{ lb/ton}$

(Equation 1)

Where:

E = Annual emissions (tons/year)

Q = Amount of Electrode Consumed (10³ lb)

EF = Emission Factor (lb/10³ lb electrode consumed) (AP-42 12.19-1)

C = Control device PM collection and removal efficiency (%)

A factor of 0.01 lb PM/lb rod may be used for TIG welding.

Use emission factors in AP-42 12.19-2 to estimate HAP emissions of manganese (Mn), nickel (Ni), chromium (Cr), cobalt (Co), and lead (Pb) emissions.

If the welding process is not identified in AP-42, Equation 2 can be used to estimate emissions.

 $E = Q \times 0.05$ lb PM/lb rod consumed x Ci x (1 - C) / 2000 lb/ton

(Equation 2)

Where:

E = Annual emissions (tons/year)

Q = Annual usage of each welding rod (lb/year)

Ci = Concentration of HAP in each welding rod (lb HAP/lb metal)

C = Control device PM collection and removal efficiency (%)

MSDS documentation contains information regarding welding rod material composition.

Louisville Metro Air Pollution Control District E43 - Welding

Plant ID:		Emission Year:	
Company Name:			
Emission Unit ID:			
Emission Process/Point I	ID:		
Shield Metal Arc Welding			
Electrode Type:	□ 5440	□ 57040	□ 50040
☐ 14Mn-4Cr ☐ E11018	☐ E410 ☐ E6010	☐ E7018 ☐ E7024	E9018 ECoCr
E308	☐ E6010	☐ E7024	ENi-Cl
E310	☐ E6012	E8018	☐ ENICrMo
E316	☐ E6013	☐ E9015	Eni-Cu
Electrode co	onsumed:	pounds	
Gas Metal Arc Welding		Flux Cored	d Welding
Electrode Type:	_	Electrode Type:	
☐ E308L	☐ E316	☐ E110	E316LT
E70S	L ENiCrMo	E11018	☐ E70T
ER5154	ERNiCu	E308LT	E71T
l_, , , , , , , , , , , , , , , , , , ,	noundo	Electrode consumed:	pounds
Electrode consumed:	pounds		
	i i		UTIOU A MALLICA
Submerge	ed Arc Welding	Tungsten Inert Gas	"TIG" Arc Welding
	ed Arc Welding		"TIG" Arc Welding
Submerge	ed Arc Welding		"TIG" Arc Welding pounds
Submerge Electrode Type EM12K	ed Arc Welding pounds	Tungsten Inert Gas Electrode consumed:	
Submerge Electrode Type EM12K	ed Arc Welding pounds	Tungsten Inert Gas	
Submerge Electrode Type EM12K	ed Arc Welding pounds	Tungsten Inert Gas Electrode consumed:	
Submerge Electrode Type EM12K Electrode consumed: Process Name:	ed Arc Welding pounds Other W	Tungsten Inert Gas Electrode consumed:	
Submerge Electrode Type EM12K Electrode consumed: Process Name: Electrode consumed:	pounds Other W pounds	Tungsten Inert Gas Electrode consumed: elding Processes	
Submerge Electrode Type EM12K Electrode consumed: Process Name: Electrode consumed:	ed Arc Welding pounds Other W	Tungsten Inert Gas Electrode consumed: elding Processes	
Submerge Electrode Type EM12K Electrode consumed: Process Name: Electrode consumed:	pounds Other W pounds	Tungsten Inert Gas Electrode consumed: elding Processes	
Submerge Electrode Type EM12K Electrode consumed: Process Name: Electrode consumed:	pounds Other W pounds	Tungsten Inert Gas Electrode consumed: elding Processes	
Submerge Electrode Type EM12K Electrode consumed: Process Name: Electrode consumed:	pounds Other W pounds	Tungsten Inert Gas Electrode consumed: elding Processes	
Submerge Electrode Type EM12K Electrode consumed: Process Name: Electrode consumed: Material Safety Data She	pounds Other W pounds	Electrode consumed: elding Processes ectrode consumed:	
Submerge Electrode Type EM12K Electrode consumed: Process Name: Electrode consumed: Material Safety Data She	pounds Other W pounds pounds cet Compositions of the el	Electrode consumed: elding Processes ectrode consumed:	

Form E43, Created 1/31/2013 Page 2 of 2